

PIXEL SILICONE EXTERIOR PROTECTION

PRODUCT DESCRIPTION

Pixel Silicone Exterior Protection is a superior quality Pure Acrylic Emulsion paint with silicone incorporated combined with biocides and good quality light-fast pigments. It provides maximum exterior protection to all buildings at any altitude severe atmospheric conditions like rain, dust, lubricating oils etc. Its satin finish makes it excellent for interior as well as exterior application. It's also suitable for wet rooms like kitchens and bathrooms, and heavily trafficked areas. It is easy to clean, and it provides resistance against algae and fungus. Resistance to rain, no watermark on the surface as water flows over the surface with excellent water-beading properties. The exceptional quality of this product will guarantee our customers long lasting performance. The guarantee is depended on doing the correct suitable surface preparation and the recommended pixel products being used during the painting process.

SURFACE PREPARATION

NEW WALLS:

The surfaces should be clean, dry and free of loose material. Apply 1 coat of HI-Opacity Undercoat followed with 2-3 coats of pixel Silicone Exterior Protection. Moisture content should be less than 16% and pH not to exceed 8-9. Surface to be free_from efflorescence

CHALKY SURFACES:

Remove loose and flaking material using nylon brush. Apply 1 coat of pixel Binder then 1 coat pixel Hi-Opacity undercoat. Finally apply 2 coats of pixel Silicone Exterior Protection.

PREVIOUSLY PAINTED SURFACES:

Sand down to a sound base, then apply two coats of pixel Silicone Exterior Protection. Allow 4 hours between coats.

SURFACES PREVIOUSLY INFECTED BY FUNGUS:

Apply one coat of pixel Fungus Wash solution. Leave for 4-6 hours then scrape off, then apply second coat and leave for 24 hours scrape off again and clean with water. (NB: Burn scrapings off site)

Apply 1 coat of pixel Binder followed by 1 coat of Hi-Opacity Undercoat, then 2 coats of pixel Silicone Exterior Protection.

FINISH	Matt
APPLICATION	Brush, Roller, or Spray
THINNING AND MIXING	Thin with clean water
EQUIPMENT CLEANING	Clean the equipment immediately with water
DRYING TIME	Dry in 3-5 hours.
COLOUR RANGE	Wide range of colors.
SPREADING CAPACITY	10-12m ² per litre
PACK SIZES	1 Litre, 4 Litres, 20 Litres.