

## PIXEL SUPER GLOSS ENAMEL

### PRODUCT DESCRIPTION AND USES

Pixel Super gloss is an alkyd-based paint designed to provide maximum durability with an excellent gloss and high gloss retention. It is an ideal for use in a variety of conditions including high humidity like coastal regions and areas of high rainfall. Pixel Super Gloss is formulated to give excellent opacity, flexibility and lightfast finish. It can be used both internally and externally on wood, metal, plaster, wallboards, brickwork, stonework etc. Pixel Super Gloss should be applied over appropriate primer and undercoat.

### SURFACE PREPARATION

#### New Work

Surfaces should be dry, clean and free from any flaky or loose materials.

Apply 1 Coat appropriate Primer.  
Apply 1 Coat universal Undercoat  
Apply 2 Coats pixel Super gloss.  
Lightly sand between coats.  
Allow overnight drying between each coat.

#### Previously painted surfaces

The surface should be clean, dry and free from loose and flaky materials. If necessary, patch prime with the appropriate primer.

Apply 1 coat universal Undercoat.  
Apply 1-2 coats Super gloss.  
Lightly sand between coats.  
Allow overnight drying between the coats.

### FINISH

Glossy

### APPLICATION

By brush or airless spray.

### THINNING AND MIXING

Thin with White Spirit or turpentine to the required consistency.

### EQUIPMENT CLEANING

Clean the equipment after use with White Spirit or turpentine.

## PIXEL SUPER GLOSS ENAMEL

**DRYING TIME**

Touch dry 4 hours. Recoatable after 16 hours.

**COLOUR RANGE**

**Wide range of colors.**

**SPREADING CAPACITY**

11 - 13m<sup>2</sup> on a smooth surface at 35-45microns DFT. It varies on a rough services.

**PACK SIZES**

1 litre, 4 litres,