

PIXEL UNIVERSAL UNDERCOAT

PRODUCT DESCRIPTION AND USES

Pixel Universal Undercoat is an alkyd-based product specifically formulated to provide a general-purpose undercoat on previously painted surface or suitable primed surface. It is used as a sandwich coat to improve intercoat adhesion between a primer and a topcoat or existing solvent based topcoat or water based topcoat. It has excellent hiding power, excellent intercoat adhesion with additional build and filling for superior protection.

It is suitable for interior and exterior use and can be applied on wood, metal, plaster, stone etc.

SURFACE PREPARATION

New Primed Metal, Wood or Plaster etc.

Ensure surface is clean and dry. Apply 1 coat of pixel universal Undercoat and allow 12 hours drying before overcoating.

Previously painted - Unsound surfaces

Remove any loose or flaky materials.

Ensure surface is clean, dry and free of other defects. Apply the appropriate patch primer to affected areas. Then slightly sand the surface to give enhanced adhesion. Apply 1 coat of Pixel universal Undercoat

Previously painted - Sound surfaces

Lightly sand. Ensure the surface is clean and apply 1 coat of Pixel Universal Undercoat.

FINISH

Matt

APPLICATION

Apply by brush, roller or spray.

THINNING AND MIXING

With White Spirit or turpentine. Stir well before use.

EQUIPMENT CLEANING

Clean the equipment immediately after use with White Spirit or turpentine

DRYING TIME

Overcoat after 12 hours.

COLOUR RANGE

Available in white.

SPREADING CAPACITY

11-13m² at 35-40 microns DFT.

PACK SIZES

1 Litre, 4 Litre

